

Also available

KAPTURE

Image and Patient Management Software

- > Manage patient and episode records
- > Live preview
- > Image processing
- > Optional upgrade for video capture and network connectivity



D-KAT

Digital Applanation Tonometer

- > Easy to read in the dark
- > Display reading to 1 decimal point
- > Reusable or disposable prisms from Keeler
- > T, R and Z-type variants available



PSL

Portable Slit Lamp

- > Big slit lamp features, portable usability
- > For domiciliary, paediatric and busy clinic use
- > Advanced optics, 10x & 16x magnification
- > Controllable illumination from maximum to zero



Symphony
by Keeler
pl Keeler
Symphony



More Keeler Instruments

Got a question? - Call us

For over ninety years we have manufactured top quality precision ophthalmic instruments.

UK: +44 (0)1753 857177

India: +91 22 6708 0400

USA: +1 610 353 4350

Brazil: +55 11 4302 6053

View our full range at

www.keeler.co.uk | www.keelerusa.com

China: +86 10 512 61868

Keeler
www.keeler-slittlamps.com

SYMPHONY DD 16061402

Keeler
www.keeler-slittlamps.com



Exceptional optics

Keeler is renowned for market-leading optics and has been dedicated to optical design and manufacture for nearly 100 years. Our customers have absolute confidence in the quality, accuracy and reliability our optical design delivers.



Let there be LEDs

A Keeler LED will provide 10,000 or more hours, giving you 100 times the life of your halogen lamp. A small additional initial investment will reap significant lifetime cost benefits.



Compare our Slit Lamp models



K series



Q series digital



Z series

illumination type	H-type tower illumination	Z-type lower illumination
Binoculars type	Galilean converging binoculars 8° or Galilean 0° parallel	
Eyepiece	12.5x	
Magnification selection	3 or 5 steps by drum rotation	
Magnification ratio Field of view	6x 34mm (5 steps only) 10x 22mm 16x 14mm 25x 8.5mm 40x 5.5mm (5 steps only)	
Interpupillary distance (PD range)	49-77mm	8° converging eye piece: 49-77mm 0° parallel eye piece: 38-85mm
Slit width	0-12mm continuously variable	0-14mm continuously variable
Slit length	0.2, 2, 3, 5, 9 & 12mm circle (1-12mm continuously variable), 1mm square	0.2, 2, 3, 5, 9 & 14mm circle, 1mm square and reserved
Filters	blue, red-free, yellow, clear, neutral density, diffuser IR heat absorbing permanently installed	blue, red-free, yellow, clear, neutral density, diffuser
Slit angle	0-180° continuous	360° continuous
Base travel	107mm X-axis, 110mm Y-axis, 25mm Z-axis	
Fixation lamp	red LED	
Illumination lamp	LED or 6V, 20W halogen lamp	LED or 12V, 30W halogen lamp
Applanation Tonometer	2414-P-2030 KAT T-type 2414-P-2040 KAT R-type 2414-P-2032 DKAT T-type, digital 2414-P-2042 DKAT R-type, digital	2414-P-2010 DKAT, Z-type, digital 2414-P-2032 DKAT, T-type, digital

Peace of mind with our 3 year warranty

